

The Bare Bones Guide to HTML



<http://werbach.com/barebones>

Version 4.0 Formatted -- February 1999

The latest version of this document is available at <http://werbach.com/barebones/>, where you will also find the text version, translations, and background materials.

The Bare Bones Guide to HTML lists all the tags that current browsers are likely to recognize. I have included all the elements in the official HTML 4.0 recommendation with common attributes, as well as Netscape and Microsoft extensions. This document is a quick reference, not a complete specification; for official information about HTML and its development, see the World Wide Web Consortium site at <http://www.w3.org/MarkUp/>.

The Guide is designed to be as concise as possible, and therefore it doesn't go into any detail about how to use the various tags. A few tags link to notes that address frequently-asked questions. If you're looking for more detailed step-by-step information, see my [WWW Help Page](#).

Table of Contents

1. INTRODUCTORY MATERIAL

- [What is unique about this guide](#)
- [Which HTML tags are included](#)
- [How this document is formatted](#) (including a description of symbols and abbreviations)

2. HTML TAGS

- [basic elements](#) (all HTML documents should have these)
- [structural definition](#) (appearance controlled by the browser's preferences)
- [presentation formatting](#) (author specifies text appearance)
- [links, graphics, and sounds](#)
- [positioning](#)
- [dividers](#)
- [lists](#)
- [backgrounds and colors](#)
- [special characters](#)
- [forms](#)
- [tables](#)
- [frames](#)
- [scripts and java](#)
- [miscellaneous](#)

Important: If you are not clear about the differences between the various versions of HTML, I suggest that you read my discussion of [the development of HTML](#), or the [World Wide Web Consortium HTML activity statement](#).

BASIC ELEMENTS

Document Type	<HTML></HTML>	(beginning and end of file)
Title	<TITLE></TITLE>	(must be in header)
Header	<HEAD></HEAD>	(descriptive info, such as title)
Body	<BODY></BODY>	(bulk of the page)

STRUCTURAL DEFINITION

	Heading	<H?></H?>	(the spec. defines 6 levels)
	Align Heading	<H? ALIGN=LEFT CENTER RIGHT></H?>	
	Division	<DIV></DIV>	
	Align Division	<DIV ALIGN=LEFT RIGHT CENTER JUSTIFY></DIV>	
4.0	Defined Content		
	Block Quote	<BLOCKQUOTE></BLOCKQUOTE>	(usually indented)
4.0	Quote	<Q></Q>	(for short quotations)
4.0	Citation	<Q CITE="URL"></Q>	
	Emphasis		(usually displayed as italic)
	Strong Emphasis		(usually displayed as bold)
	Citation	<CITE></CITE>	(usually italics)
	Code	<CODE></CODE>	(for source code listings)
	Sample Output	<SAMP></SAMP>	
	Keyboard Input	<KBD></KBD>	
	Variable	<VAR></VAR>	
	Definition	<DFN></DFN>	(not widely implemented)
	Author's Address	<ADDRESS></ADDRESS>	
	Large Font Size	<BIG></BIG>	
	Small Font Size	<SMALL></SMALL>	
4.0	Insert	<INS></INS>	(marks additions in a new version)
4.0	Time of Change	<INS DATETIME=":::"></INS>	
4.0	Comments	<INS CITE="URL"></INS>	
4.0	Delete		(marks deletions in a new version)
4.0	Time of Change	<DEL DATETIME=":::">	
4.0	Comments	<DEL CITE="URL">	
4.0	Acronym	<ACRONYM></ACRONYM>	
4.0	Abbreviation	<ABBR></ABBR>	

PRESENTATION FORMATTING

	Bold	<code></code>	
	Italic	<code><I></I></code>	
4.0*	Underline	<code><U></U></code>	(not widely implemented)
	Strikeout	<code><STRIKE></STRIKE></code>	(not widely implemented)
4.0*	Strikeout	<code><S></S></code>	(not widely implemented)
	Subscript	<code><SUB></SUB></code>	
	Superscript	<code><SUP></SUP></code>	
	Typewriter	<code><TT></TT></code>	(displays in a monospaced font)
	<u>Preformatted</u>	<code><PRE></PRE></code>	(display text spacing as-is)
	Width	<code><PRE WIDTH=?></PRE></code>	(in characters)
	<u>Center</u>	<code><CENTER></CENTER></code>	(for both text and images)
N1	Blinking	<code><BLINK></BLINK></code>	(the most derided tag ever)
	Font Size	<code></code>	(ranges from 1-7)
	Change Font Size	<code></code>	
	Font Color	<code></code>	
4.0*	Select Font	<code></code>	
N4	Point size	<code></code>	
N4	Weight	<code></code>	
4.0*	Base Font Size	<code><BASEFONT SIZE=?></code>	(from 1-7; default is 3)
MS	Marquee	<code><MARQUEE></MARQUEE></code>	

POSITIONING

N3	Multi-Column	<code><MULTICOL COLS=?></MULTICOL></code>
N3	Column Gutter	<code><MULTICOL GUTTER=?></MULTICOL></code>
N3	Column Width	<code><MULTICOL WIDTH=?></MULTICOL></code>
N3	Spacer	<code><SPACER></code>
N3	Spacer Type	<code><SPACER TYPE=HORIZONTAL VERTICAL BLOCK></code>
N3	Size	<code><SPACER SIZE=?></code>
N3	Dimensions	<code><SPACER WIDTH=? HEIGHT=?></code>
N3	Alignment	<code><SPACER ALIGN=LEFT RIGHT CENTER></code>
N4	Layer	<code><LAYER></LAYER></code>
N4	Name	<code><LAYER ID="***"></LAYER></code>
N4	Location	<code><LAYER LEFT=? TOP=?></LAYER></code>
N4	Rel. Position	<code><LAYER PAGEX=? PAGEY=?></LAYER></code>
N4	Source File	<code><LAYER SRC="***"></LAYER></code>

N4	Stacking	<LAYER Z-INDEX=?></LAYER>	
N4	Stack Position	<LAYER ABOVE="***" BELOW="***"></LAYER>	
N4	Dimensions	<LAYER HEIGHT=? WIDTH=?></LAYER>	
N4	Clipping Path	<LAYER CLIP=,,,></LAYER>	
N4	Visible?	<LAYER VISIBILITY=SHOW HIDDEN INHERIT></LAYER>	
N4	Background	<LAYER BACKGROUND="\$\$\$\$\$\$"></LAYER>	
N4	Color	<LAYER BGCOLOR="\$\$\$\$\$\$"></LAYER>	
N4	Inline Layer	<ILAYER></ILAYER>	(takes same attributes as LAYER)
N4	Alt. Content	<NOLAYER></NOLAYER>	

LINKS, GRAPHICS, AND SOUNDS

	Link Something		
	Link to Location		(if in another document)
			(if in current document)
4.0*	Target Window		
4.0*	Action on Click		(Javascript)
4.0*	Mouseover Action		(Javascript)
4.0*	Mouse out Action		(Javascript)
	Link to Email		
N, MS	Specify Subject		(use a real question mark)
	Define Location		
	Display Image		
	Alignment		
N1	Alignment		
	Alternate		(if image not displayed)
	Dimensions		(in pixels)
			(as percentage of page width/height)
	Border		(in pixels)
	Runaround Space		(in pixels)
N1	Low-Res Proxy		
	Imagemap		(requires a script)
	Imagemap		
MS	Movie Clip		
MS	Background	<BGSOUND SRC="***" LOOP=? INFINITE>	

Sound

	Client-Side Map	<MAP NAME="*" ></MAP>	(describes the map)
	Map Section	<AREA SHAPE="DEFAULT RECT CIRCLE POLY" COORDS=",,, " HREF="URL" NOHREF>	
N1	Client Pull	<META HTTP-EQUIV="Refresh" CONTENT="?; URL=URL">	
N2	Embed Object	<EMBED SRC="URL">	(insert object into page)
N2	Object Size	<EMBED SRC="URL" WIDTH=? HEIGHT=?>	
4.0	Object	<OBJECT></OBJECT>	
4.0	Parameters	<PARAM>	

DIVIDERS

	<u>Paragraph</u>	<P></P>	(closing tag often unnecessary)
	<u>Align Text</u>	<P ALIGN=LEFT CENTER RIGHT></P>	
N	Justify Text	<P ALIGN=JUSTIFY></P>	
	Line Break	 	(a single carriage return)
	Clear Textwrap	<BR CLEAR=LEFT RIGHT ALL>	
	Horizontal Rule	<HR>	
	Alignment	<HR ALIGN=LEFT RIGHT CENTER>	
	Thickness	<HR SIZE=?>	(in pixels)
	Width	<HR WIDTH=?>	(in pixels)
	Width Percent	<HR WIDTH="% ">	(as a percentage of page width)
	Solid Line	<HR NOSHADE>	(without the 3D cutout look)
N1	No Break	<NOBR></NOBR>	(prevents line breaks)
N1	Word Break	<WBR>	(where to break a line if needed)

LISTS

	Unordered List		(before each list item)
	Compact	<UL COMPACT>	
	Bullet Type	<UL TYPE=DISC CIRCLE SQUARE>	(for the whole list)
	Bullet Type	<LI TYPE=DISC CIRCLE SQUARE>	(this & subsequent)
	Ordered List		(before each list item)
	Compact	<OL COMPACT>	
	Numbering Type	<OL TYPE=A a I i 1>	(for the whole list)
	Numbering Type	<LI TYPE=A a I i 1>	(this & subsequent)
	Starting Number	<OL START=?>	(for the whole list)
	Starting Number	<LI VALUE=?>	(this & subsequent)
	Definition List	<DL><DT><DD></DL>	(<DT>=term, <DD>=definition)
	Compact	<DL COMPACT></DL>	
	Menu List	<MENU></MENU>	(before each list item)

Compact	<code><MENU COMPACT></MENU></code>	
Directory List Compact	<code><DIR></DIR></code>	(before each list item)
Compact	<code><DIR COMPACT></DIR></code>	

BACKGROUNDS AND COLORS

	Tiled Bkgnd	<code><BODY BACKGROUND="URL"></code>	
MS	Watermark	<code><BODY BGPROPERTIES="FIXED"></code>	
	Bkgnd Color	<code><BODY BGCOLOR="#\$\$\$\$\$\$"></code>	(order is red/green/blue)
	Text Color	<code><BODY TEXT="#\$\$\$\$\$\$"></code>	
	Link Color	<code><BODY LINK="#\$\$\$\$\$\$"></code>	
	Visited Link	<code><BODY VLINK="#\$\$\$\$\$\$"></code>	
	Active Link	<code><BODY ALINK="#\$\$\$\$\$\$"></code>	

(More info at <http://webach.com/web/wwwhelp.html#color>)

SPECIAL CHARACTERS

Special Character	<code>&#?;</code>	(where ? is the ISO 8859-1 code)
<code><</code>	<code>&lt;</code>	
<code>></code>	<code>&gt;</code>	
<code>&</code>	<code>&amp;</code>	
<code>"</code>	<code>&quot;</code>	
Registered TM	<code>&#174;</code>	
Registered TM	<code>&reg;</code>	
Copyright	<code>&#169;</code>	
Copyright	<code>&copy;</code>	
Non-Breaking Space	<code>&nbsp;</code>	

(Complete list at <http://www.htmlhelp.com/reference/charset>)

FORMS

	Define Form	<code><FORM ACTION="URL" METHOD=GET POST></FORM></code>	
4.0*	File Upload	<code><FORM ENCTYPE="multipart/form-data"></FORM></code>	
	Input Field	<code><INPUT TYPE="TEXT PASSWORD CHECKBOX RADIO FILE BUTTON IMAGE HIDDEN SUBMIT RESET"></code>	
	Field Name	<code><INPUT NAME="***"></code>	
	Field Value	<code><INPUT VALUE="***"></code>	
	Checked?	<code><INPUT CHECKED></code>	(checkboxes and radio boxes)
	Field Size	<code><INPUT SIZE=?></code>	(in characters)
	Max Length	<code><INPUT MAXLENGTH=?></code>	(in characters)

4.0	Button	<BUTTON></BUTTON>	
4.0	Button Name	<BUTTON NAME="***"></BUTTON>	
4.0	Button Type	<BUTTON TYPE="SUBMIT RESET BUTTON"></BUTTON>	
4.0	Default Value	<BUTTON VALUE="***"></BUTTON>	
4.0	Label	<LABEL></LABEL>	
4.0	Item Labelled	<LABEL FOR="***"></LABEL>	
	Selection List	<SELECT></SELECT>	
	Name of List	<SELECT NAME="***"></SELECT>	
	# of Options	<SELECT SIZE=?></SELECT>	
	Multiple Choice	<SELECT MULTIPLE>	(can select more than one)
	Option	<OPTION>	(items that can be selected)
	Default Option	<OPTION SELECTED>	
	Option Value	<OPTION VALUE="***">	
4.0	Option Group	<OPTGROUP LABEL="***"></OPTGROUP>	
	Input Box Size	<TEXTAREA ROWS=? COLS=?></TEXTAREA>	
	Name of Box	<TEXTAREA NAME="***"></TEXTAREA>	
N2	Wrap Text	<TEXTAREA WRAP=OFF HARD SOFT></TEXTAREA>	
4.0	Group elements	<FIELDSET></FIELDSET>	
4.0	Legend	<LEGEND></LEGEND>	(caption for fieldsets)
4.0	Alignment	<LEGEND ALIGN="TOP BOTTOM LEFT RIGHT"></LEGEND>	

TABLES

	Define Table	<TABLE></TABLE>	
4.0*	Table Alignment	<TABLE ALIGN=LEFT RIGHT CENTER>	
	Table Border	<TABLE BORDER></TABLE>	(either on or off)
	Table Border	<TABLE BORDER=?></TABLE>	(you can set the value)
	Cell Spacing	<TABLE CELLSPACING=?>	
	Cell Padding	<TABLE CELLPADDING=?>	
	Desired Width	<TABLE WIDTH=?>	(in pixels)
	Width Percent	<TABLE WIDTH=%>	(percentage of page)
4.0*	Table Color	<TABLE BGCOLOR="\$\$\$\$\$" ></TABLE>	
4.0	Table Frame	<TABLE FRAME=VOID ABOVE BELOW HSIDES LHS RHS VSIDES BOX BORDER></TABLE>	
4.0	Table Rules	<TABLE RULES=NONE GROUPS ROWS COLS ALL></TABLE>	
MS	Border Color	<TABLE BORDERCOLOR="\$\$\$\$\$" ></TABLE>	
MS	Dark Border	<TABLE BORDERCOLORDARK="\$\$\$\$\$" ></TABLE>	

MS	Light Border	<TABLE BORDERCOLORLIGHT="\$\$\$\$\$" ></TABLE>	
	Table Row	<TR></TR>	
	Alignment	<TR ALIGN=LEFT RIGHT CENTER MIDDLE BOTTOM>	
	Table Cell	<TD></TD>	(must appear within table rows)
	Alignment	<TD ALIGN=LEFT RIGHT CENTER VALIGN=TOP MIDDLE BOTTOM>	
	No linebreaks	<TD NOWRAP>	
	Columns to Span	<TD COLSPAN=?>	
	Rows to Span	<TD ROWSPAN=?>	
4.0*	Desired Width	<TD WIDTH=?>	(in pixels)
N3	Width Percent	<TD WIDTH="%">	(percentage of table)
4.0*	Cell Color	<TD BGCOLOR="#\$\$\$\$\$" >	
	Header Cell	<TH></TH>	(same as data, except bold centered)
	Alignment	<TH ALIGN=LEFT RIGHT CENTER MIDDLE BOTTOM>	
	No Linebreaks	<TH NOWRAP>	
	Columns to Span	<TH COLSPAN=?>	
	Rows to Span	<TH ROWSPAN=?>	
4.0*	Desired Width	<TH WIDTH=?>	(in pixels)
N3	Width Percent	<TH WIDTH="%">	(percentage of table)
4.0*	Cell Color	<TH BGCOLOR="#\$\$\$\$\$" >	
4.0	Table Body	<TBODY>	
4.0	Table Footer	<TFOOT></TFOOT>	(must come before THEAD)
4.0	Table Header	<THEAD></THEAD>	
	Table Caption	<CAPTION></CAPTION>	
	Alignment	<CAPTION ALIGN=TOP BOTTOM LEFT RIGHT>	
4.0	Column	<COL></COL>	(groups column attributes)
4.0	Columns Spanned	<COL SPAN=?></COL>	
4.0	Column Width	<COL WIDTH=?></COL>	
4.0	Width Percent	<COL WIDTH="%"></COL>	
4.0	Group columns	<COLGROUP></COLGROUP>	(groups column structure)
4.0	Columns Spanned	<COLGROUP SPAN=?></COLGROUP>	
4.0	Group Width	<COLGROUP WIDTH=?></COLGROUP>	
4.0	Width Percent	<COLGROUP WIDTH="%"></COLGROUP>	

FRAMES

4.0*	Frame Document	<FRAMESET></FRAMESET>	(instead of <BODY>)
4.0*	Row Heights	<FRAMESET ROWS= , , , ></FRAMESET>	(pixels or %)

4.0*	Row Heights	<FRAMESET ROWS=*></FRAMESET>	(* = relative size)
4.0*	Column Widths	<FRAMESET COLS= , , , ></FRAMESET>	(pixels or %)
4.0*	Column Widths	<FRAMESET COLS=*></FRAMESET>	(* = relative size)
4.0*	Borders	<FRAMESET FRAMEBORDER="yes no"></FRAMESET>	
4.0*	Border Width	<FRAMESET BORDER=?></FRAMESET>	
4.0*	Border Color	<FRAMESET BORDERCOLOR="#\$\$\$\$\$\$"></FRAMESET>	
N3	Frame Spacing	<FRAMESET FRAMESPACING=?></FRAMESET>	
4.0*	Define Frame	<FRAME>	(contents of an individual frame)
4.0*	Display Document	<FRAME SRC="URL">	
4.0*	Frame Name	<FRAME NAME="*" _blank _self _parent _top>	
4.0*	Margin Width	<FRAME MARGINWIDTH=?>	(left and right margins)
4.0*	Margin Height	<FRAME MARGINHEIGHT=?>	(top and bottom margins)
4.0*	Scrollbar?	<FRAME SCROLLING="YES NO AUTO">	
4.0*	Not Resizable	<FRAME NORESIZE>	
4.0*	Borders	<FRAME FRAMEBORDER="yes no">	
4.0*	Border Color	<FRAME BORDERCOLOR="#\$\$\$\$\$\$">	
4.0*	Unframed Content	<NOFRAMES></NOFRAMES>	(for non-frames browsers)
4.0	Inline Frame	<IFRAME></IFRAME>	(takes same attributes as FRAME)
4.0	Dimensions	<IFRAME WIDTH=? HEIGHT=?></IFRAME>	
4.0	Dimensions	<IFRAME WIDTH="%" HEIGHT="%"></IFRAME>	

SCRIPTS AND JAVA

	Script	<SCRIPT></SCRIPT>	
	Location	<SCRIPT SRC="URL"></SCRIPT>	
	Type	<SCRIPT TYPE="*"></SCRIPT>	
	Language	<SCRIPT LANGUAGE="*"></SCRIPT>	
4.0*	Other Content	<NOSCRIPT></NOSCRIPT>	(if scripts not supported)
	Applet	<APPLET></APPLET>	
	File Name	<APPLET CODE="*">	
	Parameters	<APPLET PARAM NAME="*">	
	Location	<APPLET CODEBASE="URL">	
	Identifier	<APPLET NAME="*">	(for references)

	Alt Text	<code><APPLET ALT="***"></code>	(for non-Java browsers)
	Alignment	<code><APPLET ALIGN="LEFT RIGHT CENTER"></code>	
	Size	<code><APPLET WIDTH=? HEIGHT=?></code>	(in pixels)
	Spacing	<code><APPLET HSPACE=? VSPACE=?></code>	(in pixels)
N4	Server Script	<code><SERVER></SERVER></code>	

MISCELLANEOUS

	Comment	<code><!-- *** --></code>	(not displayed by the browser)
	<u>Prologue</u>	<code><!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0//EN"></code>	
	Searchable	<code><ISINDEX></code>	(indicates a searchable index)
	Prompt	<code><ISINDEX PROMPT="***"></code>	(text to prompt input)
	Send Search	<code></code>	(use a real question mark)
	URL of This File	<code><BASE HREF="URL"></code>	(must be in header)
4.0*	Base Window Name	<code><BASE TARGET="***"></code>	(must be in header)
	Relationship	<code><LINK REV="***" REL="***" HREF="URL"></code>	(in header)
N4	Linked File	<code><LINK TYPE="***" SRC="***"></LINK></code>	
	Meta Information	<code><META></code>	(must be in header)
	Style Sheets	<code><STYLE></STYLE></code>	(implementations vary)
4.0	Bidirect Off	<code><BDO DIR=LTR RTL></BDO></code>	(for certain character sets)

Copyright ©1995-2001 [Kevin Werbach](http://www.werbach.com). Redistribution is permitted, so long as there is no charge and this document is included without alteration in its entirety. This Guide is not a product of Bare Bones Software. More information is available at <http://werbach.com/barebones>.



Reference **HTML Cheatsheet**

Basic Tags

`<html></html>`

Creates an HTML document

`<head></head>`

Sets off the title and other information that isn't displayed on the Web page itself

`<body></body>`

Sets off the visible portion of the document

Header Tags

`<title></title>`

Puts the name of the document in the title bar

Body Attributes

`<body bgcolor=?>`

Sets the background color, using name or hex value

`<body text=?>`

Sets the text color, using name or hex value

`<body link=?>`

Sets the color of links, using name or hex value

`<body vlink=?>`

Sets the color of followed links, using name or hex value

`<body alink=?>`

Sets the color of links on click

Text Tags

`<pre></pre>`

Creates preformatted text

`<h1></h1>`

Creates the largest headline

`<h6></h6>`

Creates the smallest headline

``

Creates bold text

`<i></i>`

Creates italic text

`<tt></tt>`

Creates teletype, or typewriter-style text

`<cite></cite>`

Creates a citation, usually italic

``

Emphasizes a word (with italic or bold)

``

Emphasizes a word (with italic or bold)

``

Sets size of font, from 1 to 7)

``

Sets font color, using name or hex value

Links

``

Creates a hyperlink

``

Creates a mailto link

``

Creates a target location within a document

``

Links to that target location from elsewhere in the document

Formatting

`<p></p>`

Creates a new paragraph

`<p align=?>`

Aligns a paragraph to the left, right, or center

**
**

Inserts a line break

<blockquote>

</blockquote>

Indents text from both sides

<dl></dl>

Creates a definition list

<dt>

Precedes each definition term

<dd>

Precedes each definition

Creates a numbered list

Precedes each list item, and adds a number

Creates a bulleted list

<div align=?>

A generic tag used to format large blocks of HTML, also used for stylesheets

Graphical Elements

Adds an image

Aligns an image: left, right, center; bottom, top, middle

Sets size of border around an image

<hr>

Inserts a horizontal rule

<hr size=?>

Sets size (height) of rule

<hr width=?>

Sets width of rule, in percentage or absolute value

<hr noshade>

Creates a rule without a shadow

</TD< tr>

Tables

<table></table>

Creates a table

<tr></tr>

Sets off each row in a table

<td></td>

Sets off each cell in a row

<th></th>

Sets off the table header (a normal cell with bold, centered text)

Table Attributes

<table border=#>

Sets width of border around table cells

<table cellspacing=#>

Sets amount of space between table cells

<table cellpadding=#>

Sets amount of space between a cell's border and its contents

<table width=# or %>

Sets width of table — in pixels or as a percentage of document width

<tr align=?> or <td align=?>

Sets alignment for cell(s) (left, center, or right)

<tr valign=?> or <td valign=?>

Sets vertical alignment for cell(s) (top, middle, or bottom)

<td colspan=#>

Sets number of columns a cell should span

<td rowspan=#>

Sets number of rows a cell should span (default=1)

<td nowrap>

Prevents the lines within a cell from being broken to fit

Frames

<frameset></frameset>

Replaces the <body> tag in a frames document; can also be nested in other framesets

<frameset rows="value,value">

Defines the rows within a frameset, using number in pixels, or percentage of width

<frameset cols="value,value">

Defines the columns within a frameset, using number in pixels, or percentage of width

<frame>

Defines a single frame — or region — within a frameset

<noframes></noframes>

Defines what will appear on browsers that don't support frames

Frames Attributes

<frame src="URL">

Specifies which HTML document should be displayed

<frame name="name">

Names the frame, or region, so it may be targeted by other frames

<frame marginwidth=#>

Defines the left and right margins for the frame; must be equal to or greater than 1

<frame marginheight=#>

Defines the top and bottom margins for the frame; must be equal to or greater than 1

<frame scrolling=VALUE>

Sets whether the frame has a scrollbar; value may equal "yes," "no," or "auto." The default, as in ordinary documents, is auto.

<frame noresize>

Prevents the user from resizing a frame

Forms

For functional forms, you'll have to run a [CGI script](#). The HTML just creates the appearance of a form.

<form></form>

Creates all forms

<select multiple name="NAME" size=?></select>

Creates a scrolling menu. Size sets the number of menu items visible before you need to scroll.

<option>

Sets off each menu item

<select name="NAME"></select>

Creates a pulldown menu

<option>

Sets off each menu item

<textarea name="NAME" cols=40 rows=8></textarea>

Creates a text box area. Columns set the width; rows set the height.

<input type="checkbox" name="NAME">

Creates a checkbox. Text follows tag.

```
<input type="checkbox" name="NAME" value="x">
```

Creates a radio button. Text follows tag

```
<input type="radio" name="NAME" value="x">
```

Creates a one-line text area. Size sets length, in characters.

```
<input type="text" name="foo" size=20>
```

Creates a Submit button

```
<input type="submit" value="NAME">
```

Creates a Submit button using an image

```
<input type="image" border=0 name="NAME" src="name.gif">
```

Creates a Reset button